

CLAIMS

1. An optical plate (12; 32) comprising on a first side a first set of at least two optical elements (14; 34) designed to bend rays (R_I) received from a light source into a beam of rays (R_{int}) that are essentially parallel to a first direction in a plane containing a main axis (AA'), characterized by means (16; 36) on the second side to bend said beam in a second direction (R_C) different from the first direction (R_{int}).
5
2. The optical plate as claimed in claim 1, in which the second side bears at least one first optical element (16; 36) to bend the beam in the second direction (R_C).
15
3. The optical plate as claimed in claim 2, in which the first optical element (16; 36) comprises at least one side (26; 42) having an orientation such that the rays in the first direction (R_{int}) are refracted in the second direction (R_C).
20
4. The optical plate as claimed in claim 3, in which the second side bears a second optical element having a side that is essentially parallel to said side of the first optical element in said plane.
25
5. The optical plate as claimed in claim 1, in which the second side includes a holographic device to bend the beam in the second direction (R_C).
30
6. The optical plate as claimed in one of claims 1 to 5, in which the optical elements (14; 34) have symmetry of revolution about the main axis (AA') and in which the second direction (R_C) is directed essentially in line with the main axis (AA').
35

7. The optical plate as claimed in one of claims 1 to 6, in which the optical elements (14) are designed to bend the rays from the source by refraction.
- 5 8. The optical plate as claimed in one of claims 1 to 6, in which the optical elements (34) each include a side (38) designed to reflect the rays (R_I) from the source in the first direction (R_{int}).
- 10 9. The optical plate as claimed in any one of claims 1 to 8, characterized in that the first set of at least two optical elements is designed to bend rays received from a light source into a beam of rays forming an angle less than or equal to 3° with the first direction.
- 15 10. The optical plate as claimed in any one of claims 1 to 9, characterized in that the second direction forms an angle greater than or equal to 10° with the first direction.
- 20 11. A projection display device comprising:
- means of generating an image (2, 4);
- means (6) of projecting the image onto a screen (10);
25 - the screen (10) comprising at least one optical plate (12; 32),
in which the optical plate (12; 32) conforms to one of claims 1 to 8.
- 30 12. The display device as claimed in claim 11, in which the projection means (6) are such that the rays (R_I) are received by the optical plate (12) with orientations (θ) relative to the general direction of the optical plate (12) varying over a continuous range of non-zero orientations relative to the main axis (AA') and in which the first direction (R_{int}) corresponds to one (θ_{int}) of the orientations of said continuous range.
- 35